

An Equation of State for Solid-Liquid-Vapor Equilibrium Applied to Gas Processing and Liquefied Natural Gas

Paolo Stringari, Marco Campestrini, Christophe Coquelet, Philippe Arpentinier

▶ To cite this version:

Paolo Stringari, Marco Campestrini, Christophe Coquelet, Philippe Arpentinier. An Equation of State for Solid-Liquid-Vapor Equilibrium Applied to Gas Processing and Liquefied Natural Gas. 13th International Conference on Properties and Phase Equilibria for Products and Process Design, May 2013, Iguazu Falls, Argentina. hal-03902885

HAL Id: hal-03902885 https://minesparis-psl.hal.science/hal-03902885

Submitted on 16 Dec 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.







An Equation of State for Solid-Liquid-Vapor Equilibrium Applied to Gas Processing and Liquefied Natural Gas

Paolo Stringari^{*}, Marco Campestrini^{*}, Christophe Coguelet^{*}, Philippe Arpentinier^{**}

*MINES ParisTech, CTP – Centre Thermodynamique des Procédés, 35 Rue Saint Honoré, 77305 Fontainebleau, France

**Air Liquide – Centre de Recherche Claude-Delorme, 1 chemin de la Porte des Loges BP 126, 78354 Jouy-en-Josas, France

ntroduction

Cryogenic processes are widely used in natural gas industry for the production of liquefied natural gas Many efforts are made by the Liquefied Natural Gas

(LNG) producing companies to ensure the safety of their plants. Despite the use of purification units, traces of pollutants can remain. These unwanted substances can form a mass of solid deposit causing dysfunctioning of the gas processing units.

In order to avoid these problems in the industrial cryogenic processes involving natural gas treatment, the accurate knowledge of thermodynamic properties like solid-liquid, liquid-vapor and solid-vapor equilibria is of a great importance.

We present a thermodynamic model, the Solid-Liquid-Vapor Peng-Robinson Equation of State (SLV PR EoS), suitable for being applied in the simulation of gas processing and LNG production thanks to its capability of accounting for the solid phase and the solid-fluid equilibrium.

This model has been used for representing phase equilibria of some pure compounds and binary mixtures of interest in the gas processing and LNG production.

193.3 K

0,6 0,7 0,8 0,9

mal P-x VLE behaviors. 161 K ≤ T ≤ 205 K – VLE; – critical line. Data [3]: VLE (□), critical line (Δ).

0,2 0,3 0,4 0,5 0,6 0,7 0,8 0,9

thermal P-x VLE behaviors. 116 K \leq T \leq 151 K. – VLE, Data: \circ Holcomb and Zollweg [5]: \times Calado and Stavely [6].

x CH4

x CH₄

the CH₄ + Kr mixture.

P [MPa] 3,5

3

2.5

2

1,5

1,1

0,9

0.8

0,7

0,6

0.4 139.1

0,3

0,2

0.1 0

0

P [MPa] 0,5 151.0K

0.1

204.6 K 201

0,2 0,3 0,4 0,5

Results for Methane + Krypton Binary System In this work, we present the qualitative comparison between the SLV PR EoS and experimental values concerning

120

115

110

100

95

0,1

P [MPa]

0.0

0,1 0,2 0,3 0,4 0,5

0

1,15,8 K

0

∑ 105

Thermodynamic model

Yokozeki [1] proposed the first EoS introducing a discontinuity in the solid-fluid transition region. This EoS presents a fourth power of volume, which allows representing all the three phases of matter with a single functional form. The fourth root is the common unphysical volume placed under the S-loop connecting the liquid and the vapor regions. The SLV PR EoS has been obtained starting from the

Yokozeki EoS in which the Peng-Robinson's attractive term has been considered; this EoS is defined as follow:

$$P(T,v) = \frac{RT}{v - c(T)} \left(\frac{v - d}{v - b}\right) - \frac{a(T)}{v^2 + 2bv - b^2}$$

P: pressure T: temperature R: gas constant v: vo a,d: parameters b: liquid covolume c: solid covolu

The proposed EoS has been used for representing phase equilibria of some pure compounds (Kr, CO₂, CH₄, C₂H₆, and C₃H₈) and binary mixtures usually involved in gas processing and LNG production.

Results for Pure Components

A pressure-temperature range has been fixed for each pure compound; each range extends from a minimum to a maximum, located on the SVE and the SLE branches, respectively. These values are indicated in Table 1. The VLE branch is instead studied between the triple and the critical points for all the pure compounds. For ethane and propane the lower limits correspond to the triple point coordinates.

Fluid	S	VE	SLE						
	Tmin / K	Pmin /Pa	Tmax / K	Pmax/MPa					
Kr	66	12	220	430					
CO ₂	170	104	310	640					
CH_4	60	16	200	600					
C_2H_6	90.359	1.14	340	4100					
C ₃ H ₈	85.53	1.7×10 ⁻⁴	380	4160					
Table 1: B T ranges for the pure compounds studied									

The quantitative comparison of the phase equilibrium values obtained with the SLV PR EoS and those from auxiliary equations [2] has been evaluated with reference to the common statistical indexes: AAD%, Bias% and MAD%. Table 2 represents these errors obtained calculating the equilibrium temperature at fixed pressure, for the compounds reported in Table 1.

Fluid	VLE			SVE			SLE				
	AAD %	BIAS %	MAD %	AAD %	BIAS %	MAD %	AAD %	BIAS %	MAD %		
Kr	0.07	-0.02	0.16	0.61	-0.61	2.02	0.19	-0.04	0.69		
CO ₂	0.04	-0.01	0.09	1.19	-1.19	4.29	0.24	-0.09	0.62		
CH ₄	0.07	-0.02	0.16	0.36	0.36	0.49	0.13	-0.03	0.32		
C ₂ H ₆	0.08	-0.01	0.22				0.03	0.01	0.07		
C ₃ H ₈	0.11	-0.02	0.24				1.41	-0.30	3.65		

Table 2: Summary of the statistical errors in calculating SVE, SLE, and VLE with the SLV PR EoS.





Conclusion and Perspectives

x CH₄

al P-x VLE, SVE, a - SLE; - VLE. - SVE;

0,1 0,2 0,3 0,4 0,5 0,6 0,7 0,8

SLE

Figure 2: Isoba

xCH₄

obaric T-x SLE behavior. – SLE. Data: • Veith and Schröder [4].

125.21

115.0 K

105.0 K

95.0 K

0,6 0,7 0,8 0.9

SLE b

0,9

VI F

85.0 K

SLE

The SLV PR EoS allows a good representation of the SLE, SVE, and VLE in a wide range of temperature and pressure for different compounds of interest in the gas processing and LNG production. The intention of the authors is to extend the study to other pure compounds and to reduce the number of the parameters included in the SLV PR EoS for an industrial application of this equation. The EoS proposed can be extended to mixtures, and allows evaluating their thermodynamic behavior in the cryogenic field. This should be an important aid for designing and optimizing industrial cryogenic processes; knowing at which conditions in a mixture the solid-fluid equilibria appears (where fluid

means either the liquid or the vapor phase) represents an opportunity of great interest, because it could be used for improving the process design and for avoiding some drawbacks as solidification of the impurities. The phase diagrams, as Px and Tx cross sections at cryogenic conditions, can give important information for evaluating new separation techniques, exploiting the capability of the SLV PR EoS in representing phase equilibrium values in which also the solid phase is involved.



[1] Yokozeki A. 2003, Analytical Equation of State for Solid-Liquid-Vapour Phases, International Journal of Thermophysics, 24: 589-620.
[2] Huber ML, McLinden MO, Lemmon EW. 2007, NIST Standard Reference Database 23, Reference Fluid Thermodynamic and Transport Properties REFPROP, Version 8.0, National Institute of Standards and Technology, Standard Reference Data Program, Gaithersburg.
[3] Calado JCG et al. 1981, Liquid-Vapor Equilibrium in the Krypton + Methane System, Journal of Chemical Society, Faraday Trans. 1, 77: 2503-2513. [4] Veith H and Schröder E. 1937, Schmelzdiagramme Einiger Binärer Systeme aus Kondensierten Gasen, Z. Phys. Chem. Abt. A, 179: 16-22.
 [5] Hokomb CD and Zollweg JA. 1992, Comparison of Interfacial Tension and Capillary Constant for Argon + Krypton, CH₄ + Krypton, and C₂H₆ Krypton Using Two Independent Methods of Measurement, Fluid Phase Equilibriar, 75: 213-224.
 [6] Calado JCG and Steveley LAK. Thermodynamics of Liquid Mixtures of Krypton and Methane, Trans. Faraday Society, 67: 1261-1269.



Properties and Phase Equilibria for Product and Process Design

nal P-x cross sections: VLE; SLE; SLE; SVE



ID:128