



HAL
open science

CERN PROTON IRRADIATION FACILITY (IRRAD) DATA MANAGEMENT, CONTROL AND MONITORING SYSTEM INFRASTRUCTURE FOR POST-LS2 EXPERIMENTS

Blerina Gkotse, Pierre Jouvelot, Giuseppe Pezzullo, Federico Ravotti

► **To cite this version:**

Blerina Gkotse, Pierre Jouvelot, Giuseppe Pezzullo, Federico Ravotti. CERN PROTON IRRADIATION FACILITY (IRRAD) DATA MANAGEMENT, CONTROL AND MONITORING SYSTEM INFRASTRUCTURE FOR POST-LS2 EXPERIMENTS. The 19th Biennial International Conference on Accelerator and Large Experimental Physics Control Systems (ICALEPCS 2023), Oct 2023, Cape Town, South Africa, South Africa. hal-04271482

HAL Id: hal-04271482

<https://minesparis-psl.hal.science/hal-04271482v1>

Submitted on 6 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Blerina Gkotse^{1,2}, Pierre Jouvelot², Giuseppe Pezzullo¹, Federico Ravotti¹

¹ Experimental Physics Department, CERN, Geneva, Switzerland

² Mines Paris, PSL University, Paris, France

ABSTRACT

Since upgrades of the CERN Large Hadron Collider are planned and design studies for a post-LHC particle accelerator are ongoing, it is key to ensure that the detectors and electronic components used in the CERN experiments and accelerators can withstand the high amount of radiation produced during particle collisions. To comply with this requirement, scientists perform radiation testing experiments, which consist in exposing these components to high levels of particle radiation to simulate the real operational conditions. The CERN Proton Irradiation Facility (IRRAD) is a well-established reference facility for conducting such experiments. Over the years, the IRRAD facility has developed a dedicated software infrastructure to support the

control and monitoring systems used to manage these experiments, as well as to handle other important aspects such as dosimetry, spectrometry, and material traceability. In this paper, new developments and upgrades to the IRRAD software infrastructure are presented. These advances are crucial to ensure that the facility remains up-to-date and able to cope with the increasing (and always more complex) user needs. These software upgrades (some of them carried out within the EU-funded project AIDAInnova and EURO-LABS) will help to improve the efficiency and accuracy of the experiments performed at IRRAD and enhance the capabilities of this facility.

PROTON IRRADIATION FACILITY IRRAD

- **Qualification of radiation hardness** of materials, detectors, and electronic systems for High-Energy Physics experiments
- **Proton beam of 24 GeV/c**
- Beam of Gaussian shape with typical size of 12x12 mm² FWHM
- 5x10¹¹ p/spill, 8x10¹¹ p/spill from 2024!
- Spills of 400 ms every ~10 s
- Fluence of ~1.4 x 10¹⁶ p/cm² in a week
- Scanning also in dimensions of 10x10 cm²
- Low-temperature irradiation (-25°C)
- Irradiation down to 4.2 K using Cryostat with LHe
- 8 IRRAD Tables, 1 Shuttle, 2 cold-boxes

cern.ch/ps-irrad

DATA MANAGEMENT

IRRAD Data Manager – IDM: A unified data management tool for Irradiation Experiments follow-up: <http://cern.ch/idm>

IDM screenshots with the main functionalities:

- Registration
- Planning
- Operation
- Dosimetry
- Traceability
- History

Testing CAEN RadHAND device and API to be integrated with IDM

RFIDs being tested for sample tagging

Fluence results calculated and displayed in IDM

BEAM DATA MONITORING AND LOGGING

Fixed-BPM for beam alignment purpose
39 pads of 4x4 mm²

Mini-BPM (9 pads of 4x4 mm²) and single-pad BPM (1 pad of 4x4 mm²) for aligning IRRAD tables to the beam

Beam Profile display <https://cern.ch/opwt/irrad/>

Beam Profile logging display in Timber

VIRTUALIZATION

Using CERN OpenStack for servers' deployment:

- BPM & CMW Server (Production and Test)
- Dose monitoring
- Apex Gamma Server (Canberra Genie 2000)
- Apex Gamma MS SQL Server

Advantages:

- Minimizing hardware computer failures
- Minimising additional costs
- Improving resilience
- Redundancy

IRRAD Openstack project

CONTROL AND MONITORING SYSTEMS

Brainboxes (Ethernet to Serial)

Motor Control Unit

IRRAD Table

Graphical User Interface (GUI)

Redesign and redeployment of IRRAD Table Control GUI interface

New IRRAD Table Control GUI compatible with Linux and with database in the backend

New lightweight shuttle Control GUI interface compatible with Linux

Monitoring IRRAD positions and temperatures

SUMMARY AND FUTURE WORK

Summary

- IRRAD is a reference facility in HEP, handling several experiments and samples
- IRRAD Data Manager (IDM) was built and deployed to facilitate the data handling of the irradiation experiments, currently being deployed also in other facilities
- New functionalities were developed in IDM to cover users' requirements and be compliant with the CERN IT infrastructure and security
- New BPM Controls Middleware (CMW) server was put in production to publish data in NXCALs, making data available in Timber
- New BPM sensors were installed in IRRAD
- Virtual Machines were deployed for running IRRAD servers
- New developments for the IRRAD control system GUIs and upgrades of the old ones
- Monitoring of Temperatures, dose rates and humidity

Future Work

- Aiming to complete the IDM generalization for other facilities
- Testing RFID tags and CAEN RadHAND for possible use in IRRAD
- A new IRRAD-BPM DAQ (scalable system) is developed and will be installed in IRRAD for the run 2024
- A new classifier of beam quality is foreseen

