



**HAL**  
open science

## Comparative study of kapok-based self supported composites with TiO<sub>2</sub> or SiO<sub>2</sub> usable in Li-ion batteries

Julia Wagner, K. Guérin, Sandrine Berthon-Fabry

### ► To cite this version:

Julia Wagner, K. Guérin, Sandrine Berthon-Fabry. Comparative study of kapok-based self supported composites with TiO<sub>2</sub> or SiO<sub>2</sub> usable in Li-ion batteries. ISICXXI: 21st International Symposium on Intercalation Compounds, Jun 2023, Nancy, France. hal-04320414

**HAL Id: hal-04320414**

**<https://minesparis-psl.hal.science/hal-04320414>**

Submitted on 4 Dec 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Comparative study of kapok-based self supported composites with TiO<sub>2</sub> or SiO<sub>2</sub> usable in Li-ion batteries

Julia Wagner<sup>\*1,2</sup>, Katia Guérin<sup>2,1</sup>, Sandrine Berthon-Fabry<sup>1</sup>

<sup>1</sup> MINES Paris, PSL University, PERSEE, CS 10207 rue Claude Daunesse 06904 Sophia Antipolis Cedex, France<sup>2</sup>


Clermont Université, ICCF, F-63000 Clermont-Ferrand, France

(\*) julia.wagner@minesparis.psl.eu

Biobased and recycled materials are becoming more commonly used to create anodes for lithium-ion batteries. [1], [2], [3] Carbon-based materials can be obtained by pyrolyzing organic materials while keeping their initial shape. [4] In this work, we synthesized self-supported carbon-metal oxide composites using pyrolyzed kapok fibers. We chose two well known anode materials: TiO<sub>2</sub> processing through insertion and SiO<sub>2</sub> processing through conversion-alloying process. The main idea is to compare the efficiency and durability of self-supported anodes upon electrochemical mechanisms.

The TiO<sub>2</sub>-based composite was synthesized by sol-gel. In order to reach the theoretical capacity of TiO<sub>2</sub> the physico-chemical properties of the composite were optimized. The lithium-ion-conducting anatase phase was obtained by modifying the acid used as a sol-gel catalyst and the pyrolysis temperature. The specific surface area and the material texture were varied by testing two drying processes (evaporative and CO<sub>2</sub> supercritical drying) and different thermal treatments. Finally, the optimal synthesis method was determined by galvanostatic cycling of the anodes.

The SiO<sub>2</sub>-based composite was obtained from the pyrolysis of a silica-resorcinol-formaldehyde gel. Following the same methodology as TiO<sub>2</sub>, different synthesis parameters were optimized. Specifically, in order to increase durability of the anode the effects of silica content, specific surface area and morphology were tuned by adjusting reagent and catalyst quantities. Finally, the optimal synthesis conditions were determined by galvanostatic cycling.



A: N<sub>2</sub> adsorption isotherms of C-TiO<sub>2</sub> and C-SiO<sub>2</sub> composites, B, C: SEM micrographs of C-TiO<sub>2</sub> (B) and C-SiO<sub>2</sub> (C) composites

## References

- [1] D. K. Sam et al., Carbohydrate Research, **vol. 491** (2020), p. 107986,
- [2] A. K. Naskar et al, RSC Adv., **vol. 4**, n° 72 (2014), p. 38213- 38221
- [3] S. Mei et al., Applied Surface Science, **vol. 563** (2021), p. 150280,
- [4] Z. Lin et al, Chem. Rec., **vol. 20**, n°4 (2020), p. 187- 208